



**USA Supplier:**

JMC Plumbing & Venting Products Inc.  
6235 Judson Street  
Lincoln, NE 68507

**SPECIFICATION SHEET**  
**V7-31 HR D UV WHITE**

**APPLICATIONS:** Injection Molded

	TEST METHOD	VALUE
<b>PHYSICAL PROPERTIES</b>		
Specific Gravity (+/- 0.02)	ASTM D792	MSRP <b>29.99</b>
Hardness (Shore D +/- 3)	ASTM D 2240	Instantaneous <b>80</b>

<b>MECHANICAL PROPERTIES</b>		
Tensile Strength (PSI)	ASTM D638	<b>7,100</b>
Tensile Modulus (PSI)	ASTM D638	<b>410,000</b>
Flexural Strength (PSI)	ASTM D790	<b>13,000</b>
Izod Impact, FT-LB/IN NOTCH	ASTM D256	<b>1.50</b>
Heat Distortion Temperature@264PSI °C(°F)	ASTM D635	<b>160</b>
Flammability -- Meets UL-94	V-0 CLASSIFICATION	

**Important**  
We believe these tests to be reliable and accurate to the best of our knowledge but cannot warranty for processes and applications beyond our control.  
This compound is UV stabilized.

**CrownVentGuard™ Critter Vent Cap**

Part No - M05 -141  
UPC - 783495025108  
SKU: 05-085

**Description:**

- Prevents Debris, Critters From Entering Into Vent Pipe
- Made In The USA
- Made from high-impact PVC Schedule 40 Plastic
- Quick & Easy to install
- Fits Standard 3" & 4" ABS & PVC vent pipe
- For DWV, & Radon applications
- 1/2" Ventilation holes meet all Radon standards
- Protects Radon fan exhaust
- Installed at the terminus of a Radon mitigation system
- Solution to prevent Roof vent pipe blockages and clogs
- All Residential and Commercial installations
- PVS Vent Pipe and Ultraviolet (UV) Protection

<b>SPECIFICATIONS</b>	
Color:	<b>Black &amp; White</b>
Material:	<b>PVC Schedule 40</b>
Brand:	<b>CrownVentGuard™</b>
Pipe Size:	<b>3" or 4" in.</b>
Weight:	<b>0.5 lb.</b>



**Attaches To Existing Roof Vent Pipe**

