

HERO 120H

Fresh Air Appliance - HRV

Product #: 99400



Fantech's most efficient series yet! The HERO 120H is ideal for high-rise apartment applications, condominiums, single and multi family homes. With a completely new design the HERO 120H features a Counterflow core, round metal collars and an high efficiency rating!

Features

- 5" (125mm) round metal duct connections with rubberized duct seals
- Removable screw terminal for easy connection with external access
- Top port design fits in tight spaces
- Includes speed bracket
- Counterflow heat recovery core
- Multiple speed operation
- Internal recirculation defrost
- Integrated MERV-8 Filter
- 41.4 lbs (18.8 kg) including core

Optional Controls:

- ECO-TOUCH® (#44929) – Programmable Touch Screen Wall Control
- EDF7 (#44883) – Electronic multi-function dehumidistat
- EDF1R (#40393) – Multi-function dehumidistat
- RTS2 (#40164) – 20 minute timer over-ride
- RTS5 (#44794) – 20/40/60 minute timer
- MDEH1 (#40172) – Dehumidistat

Specifications

- Duct size – 5" (125mm) round
- Voltage/Phase – 120/1
- Power rated – 165 W
- Amp – 1.2 A
- Average airflow – 118 cfm (56 L/s)
@ 0.3" P_s (75 Pa)

Fans

Two (2) factory-balanced fans with backward curved blades. Motors come with permanently lubricated, sealed ball-bearings to guarantee long life and maintenance-free operation.

Heat Recovery Core

Counterflow heat recovery exchanger built from thermoformed polymer plates covered by a limited lifetime warranty. Core dimensions are 14.4" x 14.4" (366 x 366 mm) with a 10" (255 mm) depth. Our heat exchangers are designed and manufactured to withstand extreme temperature variations.

Winterguard™ Defrost

The unit incorporates a unique and quiet internal recirculation defrost that does not depressurize the home during the defrost cycle. A preset defrost sequence is activated when the outdoor temperature falls below 23° F (-5° C) and automatically adjusts itself based on operating conditions. The fan speed is also adjusted automatically to provide a smooth and quiet transition between Ventilation & Defrost mode.

Serviceability

Core, filters, fans and electronic panel can be accessed easily from the access panel. Core conveniently slides out with only 12" (305 mm) clearance.

Duct Connections

5" (125mm) round metal duct connections with rubberized seal.

Case

24 gauge galvanized pre-painted steel corrosion resistant

Insulation

Cabinet is fully insulated with 3/4" (20 mm) high density expanded polystyrene.





Filters

Two (2) washable electrostatic panel type air filters 7.87" (200mm) x 9.84" (250mm) x 0.125" (3mm). An added MERV-8 supply filter is supplied with the unit. MERV-8 dimensions 3.48" x 10.12" x 1.75" (88.5mm x 257mm x 44.5mm)

Warranty

Limited lifetime on counterflow exchanger, 7 year on motors, and 5 year on parts.

Dimensions & Airflow




Model	A		B		C		D	
	in	mm	in	mm	in	mm	in	mm
HERO 120H	23 1/4	590	11 1/2	291	22 5/8	575	24 1/4	616

Dimensional information is in inches. Clearance of 12" (305mm) in front of the unit is recommended for removal of core. All units feature three foot plug-in power cord with 3-prong plug.

Ventilation Performance

in. wg. (Pa)	0.1 (25)	0.2 (50)	0.3 (75)	0.4 (100)	0.5 (125)	0.6 (150)	0.7 (175)	0.8 (200)
	cfm (L/s)	cfm (L/s)	cfm (L/s)	cfm (L/s)	cfm (L/s)	cfm (L/s)	cfm (L/s)	cfm (L/s)
Net supply airflow	133 (63)	125 (59)	119 (56)	110 (52)	102 (48)	91 (43)	83 (39)	72 (34)
Gross supply airflow	136 (64)	127 (60)	121 (57)	112 (53)	104 (49)	93 (44)	85 (40)	74 (35)
Gross exhaust airflow	136 (64)	127 (60)	121 (57)	112 (53)	104 (49)	93 (44)	85 (40)	74 (35)

Ventilation performance results were obtained without the MERV-8 filter installed.



Energy performance

Heating	Supply temperature		Net airflow		Consumed power	Sensible recovery efficiency	Ajusted Sensible recovery efficiency	Apparent sensible effectiveness	Latent recovery/moisture transfer
	°F	°C	cfm	L/s	W	%	%	%	-
	32	0	70	33	60	80	86	89	0.01
	32	0	100	47	105	75	83	85	0.01
	32	0	117	55	160	70	79	81	0.02
	-13	-25	68	32	100	63	67	95	0.05

Energy performance results were obtained without the MERV-8 filter installed.

Requirements and standards

- Complies with the UL 1812 requirements regulating the construction and installation of Heat Recovery Ventilators
- Complies with the CSA C22.2 no. 113 Standard applicable to ventilators
- Complies with the CSA F326 requirements regulating the installation of Heat Recovery Ventilators
- Technical data was obtained from published results of test relating to CSA C439 Standards
- HVI certified and ENERGY STAR® qualified*

* This product earned the ENERGY STAR® by meeting strict efficiency guidelines set by Natural Resources Canada and the US EPA. It meets ENERGY STAR® requirements only when used in Canada.

Contacts

Submitted by: _____	Date: _____
Quantity: _____	Model: _____
Comments: _____	Project #: _____
Location: _____	
Architect: _____	
Engineer: _____	Contractor: _____

Distributed by:

United States 10048 Industrial Blvd. • Lenexa, KS 66215 • 1.800.747.1762 • www.fantech.net

Canada 50 Kanafllakt Way • Bouctouche, NB E4S 3M5 • 1.800.565.3548 • www.fantech.net

Systemair reserves the right to modify, at any time and without notice, any or all of its products' features, designs, components and specifications to maintain their technological leadership position.



fantech®
a systemair company