



USA Supplier:

JMC Plumbing & Venting Products Inc.
6235 Judson Street
Lincoln, NE 68507

SPECIFICATION SHEET V7-31 HR D UV WHITE

APPLICATIONS: Injection Molded

	TEST METHOD	VALUE
PHYSICAL PROPERTIES		
Specific Gravity (+/- 0.02)	ASTM D792	MSRP 29.99
Hardness (Shore D +/- 3)	ASTM D 2240	Instantaneous 80

MECHANICAL PROPERTIES

Tensile Strength (PSI)	ASTM D638	7,100
Tensile Modulus (PSI)	ASTM D638	410,000
Flexural Strength (PSI)	ASTM D790	13,000
Izod Impact, FT-LB/IN NOTCH	ASTM D256	1.50
Heat Distortion Temperature@264PSI °C(°F)	ASTM D635	160
Flammability -- Meets UL-94	V-0 CLASSIFICATION	

Important

We believe these tests to be reliable and accurate to the best of our knowledge but cannot warranty for processes and applications beyond our control.
This compound is UV stabilized.

CrownVentGuard™ Critter Vent Cap

Part No - M05 -141
UPC - 783495025108
SKU: 05-085

Description:

- Prevents Debris, Critters From Entering Into Vent Pipe
- Made In The USA
- Made from high-impact PVC Schedule 40 Plastic
- Quick & Easy to install
- Fits Standard 3" & 4" ABS & PVC vent pipe
- For DWV, & Radon applications
- 1/2" Ventilation holes meet all Radon standards
- Protects Radon fan exhaust
- Installed at the terminus of a Radon mitigation system
- Solution to prevent Roof vent pipe blockages and clogs
- All Residential and Commercial installations
- PVS Vent Pipe and Ultraviolet (UV) Protection

SPECIFICATIONS

Color:	Black & White
Material:	PVC Schedule 40
Brand:	CrownVentGuard™
Pipe Size:	3" or 4" in.
Weight:	0.5 lb.



**Attaches To Existing
Roof Vent Pipe**

